

SAFETY DATA SHEET

(in accordance with Regulation (EU) No 453/2010)

MF-XXX -Merlin Fuel



Version: 1
Revision date: 12/05/2016

Page 1 of 11
Print date: 12/05/2016

SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: Merlin Fuel
Product Code: MF-XXX

1.2 Relevant identified uses of the mixture and uses advised against.

RC Fuel

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: **Alavesa de Barnices, s.a.**
Address: Cmno. del Prado, 2
City: Oyón
Province: Álava
Telephone: +34 945 601 836
Fax: +34 945 622 136
E-mail: alaba@alaba.es
Web: www.alaba.es

1.4 Emergency telephone number: +34 945 60 18 36 (Only available during office hours; Monday-Friday; 08:00-18:00)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the mixture.

In accordance with Regulation (EU) No 1272/2008:

- Acute Tox. 3 : Toxic in contact with skin or if inhaled.
- Acute Tox. 3 : Toxic if inhaled.
- Acute Tox. 3 : Toxic if swallowed, in contact with skin or if inhaled.
- Flam. Liq. 2 : Highly flammable liquid and vapour.
- STOT SE 1 : Causes damage to organs.

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:



Signal Word:

Danger

H statements:

- H225 Highly flammable liquid and vapour.
- H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled.
- H370 Causes damage to organs.

P statements:

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P270 Do not eat, drink or smoke when using this product.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/...
- P302+P352 IF ON SKIN: Wash with plenty of water/...

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) No 453/2010)

MF-XXX -Merlin Fuel

Version: 1

Revision date: 12/05/2016



Page 2 of 11

Print date: 12/05/2016

Contains:
methanol

2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	specific concentration limit
Index No: 603-001-00-X CAS No: 67-56-1 EC No: 200-659-6 Registration No: 01-2119433307-44-XXXX	[1] methanol	30 - 75 %	Acute Tox. 3 *, H311 - Acute Tox. 3 *, H331 - Acute Tox. 3 *, H301 - Flam. Liq. 2, H225 - STOT SE 1, H370 **	STOT SE 1, H370: C ≥ 10 % STOT SE 2, H371: 3 % ≤ C < 10 %
Index No: 609-036-00-7 CAS No: 75-52-5 EC No: 200-876-6	[1] nitromethane	1 - 50 %	Acute Tox. 4 *, H302 - Flam. Liq. 3, H226	-

(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

*, ** See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

[1] Substance with a Community workplace exposure limit (see section 8.1).

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

If wearing contact lenses, remove them. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eye contact.

If wearing contact lenses, remove them. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. **NEVER** use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. **NEVER** induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Toxic Product, accidental contact may result in serious respiratory difficulties, alteration of the central nervous system and in extreme cases, unconsciousness. Immediate medical assistance is required.

4.3 Indication of any immediate medical attention and special treatment needed.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) No 453/2010)

MF-XXX -Merlin Fuel

Version: 1

Revision date: 12/05/2016



Page 3 of 11

Print date: 12/05/2016

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

SECTION 5: FIREFIGHTING MEASURES.

The product is Highly inflammable, it can cause or considerably worsen a fire, the necessary prevention measures should be taken and risks avoided. In case of fire, the following measures are recommended:

The product is NOT classified as flammable, in case of fire the following measures should be taken:

5.1 Extinguishing media.

Recommended extinguishing methods.

Extinguisher powder or CO₂. In case of more serious fires, also alcohol-resistant foam and water spray. Do not use a direct stream of water to extinguish.

5.2 Special hazards arising from the mixture.

Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and gloves.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

Eliminate possible ignition points and ventilate the area. Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Pick up the spill with non-combustible absorbent materials (soil, sand, vermiculite, diatomite, etc.). Pour the product and the absorbent in an appropriate container. The contaminated area should be immediately cleaned with an appropriate decontaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

For personal protection, see section 8. Never use pressure to empty the containers. They are not pressure-resistant containers.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 35° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorized persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) No 453/2010)

MF-XXX -Merlin Fuel

Version: 1
Revision date: 12/05/2016



Page 4 of 11
Print date: 12/05/2016

Ninguno

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
methanol	67-56-1	European Union [1]	Eight hours	200 (skin)	260 (skin)
			Short term		
		United Kingdom [2]	Eight hours	200	266
			Short term	250	333
nitromethane	75-52-5	United Kingdom [2]	Eight hours	100	254
			Short term	150	381

[1] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

[2] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adopted by Health and Safety Executive.

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
methanol N. CAS: 67-56-1 N. CE: 200-659-6	DNEL (Workers)	Inhalation, Long-term, Local effects	260 (mg/m ³)
	DNEL (General population)	Inhalation, Long-term, Local effects	50 (mg/m ³)
	DNEL (Workers)	Inhalation, Long-term, Systemic effects	260 (mg/m ³)
	DNEL (General population)	Inhalation, Long-term, Systemic effects	50 (mg/m ³)
	DNEL (Workers)	Dermal, Long-term, Systemic effects	40 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	8 (mg/kg bw/day)
	DNEL (Workers)	Dermal, Acute, Systemic effects	40 (mg/kg bw/day)
	DNEL (General population)	Dermal, Acute, Systemic effects	8 (mg/kg bw/day)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
methanol N. CAS: 67-56-1 N. CE: 200-659-6	aqua (freshwater)	20,8 (mg/L)
	aqua (marine water)	2,08 (mg/L)
	aqua (intermittent releases)	1540 (mg/L)
	STP	100 (mg/L)
	sediment (freshwater)	77 (mg/kg sediment dw)
	sediment (marine water)	7,7 (mg/kg sediment dw)
	soil	3,18 (mg/kg soil dw)

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

8.2 Exposure controls.

Measures of a technical nature:

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) No 453/2010)

MF-XXX -Merlin Fuel

Version: 1

Revision date: 12/05/2016



Page 5 of 11

Print date: 12/05/2016

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %
Uses:	RC Fuel
Breathing protection:	
PPE:	Filter mask for protection against gases and particles.
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.
CEN standards:	EN 136, EN 140, EN 405
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.
Observations:	Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.
Filter Type needed:	A2
Hand protection:	
PPE:	Non-disposable protective gloves against chemicals.
Characteristics:	«CE» marking, category III. Check the list of chemicals for which the glove has been tested.
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420
Maintenance:	A schedule for the periodical replacement of gloves should be established in order to guarantee their replacement before pollutants permeate them. The use of contaminated gloves could be more dangerous than not using gloves, since the pollutant can gradually accumulate in the glove's material.
Observations:	They are to be replaced whenever tears, cracks or deformations are observed or when exterior dirt could reduce their strength.
Material:	PVC (polyvinyl chloride)
Breakthrough time (min.):	> 480
Material thickness (mm):	0,35
Eye protection:	
If the product is handled correctly, no individual protection equipment is necessary.	
Skin protection:	
PPE:	Chemical protective clothing
Characteristics:	«CE» marking, category III. Clothing should fit properly. The level of protection must be set according to a test parameter called BT (Breakthrough Time), which indicates how long it takes for the chemical to pass through the material.
CEN standards:	EN 464, EN 340, EN 943-1, EN 943-2, EN ISO 6529, EN ISO 6530, EN 13034
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.
Observations:	The protective clothing's design should facilitate correct positioning, staying in place without moving for the period of use expected, bearing in mind environmental factors as well as any movement or position the user might adopt while carrying out the activity.
PPE:	Anti-static safety footwear against chemicals.
Characteristics:	«CE» marking, category III. Check the list of chemicals against which the footwear is resistant.
CEN standards:	EN ISO 13287, EN 13832-1, EN 13832-2, EN 13832-3, EN ISO 20344, EN ISO 20345
Maintenance:	For correct maintenance of this kind of safety footwear, it is necessary to observe the instructions specified by the manufacturer. The footwear should be replaced as soon as any sign of damage is observed.
Observations:	The footwear should be cleaned regularly and dried when damp, although it should not be placed too close to a source of heat in order to avoid any sharp changes in temperature.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Appearance: Liquid with characteristic odour

Colour: N.A./N.A.

Odour: N.A./N.A.

Odour threshold: N.A./N.A.

pH: N.A./N.A.

Melting point: N.A./N.A.

Boiling Point: 68 °C

Flash point: 15 °C

Evaporation rate: N.A./N.A.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) No 453/2010)

MF-XXX -Merlin Fuel



Version: 1
Revision date: 12/05/2016

Page 6 of 11
Print date: 12/05/2016

Inflammability (solid, gas): N.A./N.A.
Lower Explosive Limit: N.A./N.A.
Upper Explosive Limit: N.A./N.A.
Vapour pressure: 109,999
Vapour density:N.A./N.A.
Relative density:0,864 g/cm³
Solubility:N.A./N.A.
Liposolubility: N.A./N.A.
Hydrosolubility: N.A./N.A.
Partition coefficient (n-octanol/water): N.A./N.A.
Auto-ignition temperature: N.A./N.A.
Decomposition temperature: N.A./N.A.
Viscosity: N.A./N.A.
Explosive properties: N.A./N.A.
Oxidizing properties: N.A./N.A.
N.A./N.A. = Not Available/Not Applicable due to the nature of the product

9.2. Other information.

VOC content (p/p): 90 %
VOC content: **777,489** g/l

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Unstable in contact with:

- Acids.
- Bases.
- Oxidizing agents.

10.3 Possibility of hazardous reactions.

In certain conditions this may cause a polymerization reaction.

10.4 Conditions to avoid.

Avoid the following conditions:

- Heating.
- High temperature.
- Contact with incompatible materials.

10.5 Incompatible materials.

Avoid the following materials:

- Acids.
- Bases.
- Oxidizing agents.

10.6 Hazardous decomposition products.

Depending on conditions of use, can be generated the following products:

- COx (carbon oxides).
- Organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION.

11.1 Information on toxicological effects.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Splatters in the eyes can cause irritation and reversible damage.

Toxicological information about the substances present in the composition.

Name	Acute toxicity
------	----------------

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) No 453/2010)

MF-XXX -Merlin Fuel



Version: 1
Revision date: 12/05/2016

Page 7 of 11
Print date: 12/05/2016

	Type	Test	Kind	Value
methanol CAS No: 67-56-1 EC No: 200-659-6	Oral	LD50	Rat	5630 (mg/kg bw) [1] [1] Gigiena Truda i Professional'nye Zabolevaniya. Labor Hygiene and Occupational Diseases. Vol. 19(11), Pg. 27, 1975
	Dermal	LD50	Rabbit	15800 (mg/kg bw) [1] [1] Raw Material Data Handbook, Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 74, 1974
	Inhalation	LC50	Rat	83.9 (mg/l) [1] [1] Raw Material Data Handbook, Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 74, 1974

a) acute toxicity;

Product classified:

Acute toxicity (Dermal), Category 3: Toxic in contact with skin.

Acute toxicity (Inhalation), Category 3: Toxic if inhaled.

Acute toxicity (Oral), Category 3: Toxic if swallowed.

Acute Toxicity Estimate (ATE):

:

ATE (Dermal) = 462 mg/kg

ATE (Inhalation) = 1077 mg/l/4 h (Gases)

ATE (Inhalation) = 5 mg/l/4 h (Fumes)

ATE (Oral) = 143 mg/kg

b) skin corrosion/irritation;

Not conclusive data for classification.

c) serious eye damage/irritation;

Not conclusive data for classification.

d) respiratory or skin sensitisation;

Not conclusive data for classification.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Not conclusive data for classification.

h) STOT-single exposure;

Product classified:

Specific target organ toxicity following a single exposure, Category 1: Causes damage to organs.

i) STOT-repeated exposure;

Not conclusive data for classification.

j) aspiration hazard;

Not conclusive data for classification.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

Name	Ecotoxicity			
	Type	Test	Kind	Value

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) No 453/2010)

MF-XXX -Merlin Fuel



Version: 1

Revision date: 12/05/2016

Page 8 of 11

Print date: 12/05/2016

methanol CAS No: 67-56-1 EC No: 200-659-6	Fish	LC50	Trachinotus carolinus	10112 (mg/L) [1]
			[1] Baltz, D. M. et al., Transactions of the American Fisheries Society 134: 730-740, 2005	
	Aquatic invertebrates	EC50	Daphnia magna	20803 (mg/L) [1]
			[1] Environmental Toxicology and Chemistry 14(12): 2085-2088, 1995	
	Aquatic plants	EC50	Selenastrum capricornutum	22000 (mg/L) [1]
			[1] Ecotoxicology and Environmental Safety 71: 166-1711, 2008	

12.2 Persistence and degradability.

No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
	Log Pow	BCF	NOECs	Level
methanol N. CAS: 67-56-1 EC No: 200-659-6	-0,74	-	-	Very low
nitromethane N. CAS: 75-52-5 EC No: 200-876-6	-0,35	-	-	Very low

12.4 Mobility in soil.

No information is available about the mobility in soil.
The product must not be allowed to go into sewers or waterways.
Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13 DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.
Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

Sea: Transport by ship: IMDG.

Transport documentation: Bill of lading

Air: Transport by plane: ICAO/IATA.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) No 453/2010)

MF-XXX -Merlin Fuel



Version: 1
Revision date: 12/05/2016

Page 9 of 11
Print date: 12/05/2016

Transport document: Airway bill.

14.1 UN number.

UN No: UN1992

14.2 UN proper shipping name.

Description: UN 1992, FLAMMABLE LIQUID, TOXIC, N.O.S. (CONTAINS METHANOL / NITROMETHANE), 3 (6.1), PG II, (D/E)

14.3 Transport hazard class(es).

Class(es): 3

14.4 Packing group.


Packing group: II

14.5 Environmental hazards.

Marine pollutant: No

14.6 Special precautions for user.

ADR LQ: 1 L



Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.
Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-E,S-D
Proceed in accordance with point 6.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code.

The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

See annex I of the Directive 96/82/EC of 9 December 1996 on the control of major-accident hazards involving dangerous substances.

The product is not affected by Directive 2012/18/EU (SEVESO III).

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

15.2 Chemical safety assessment.

There has been no evaluation a chemical safety assessment of the product.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H370	Causes damage to organs.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) No 453/2010)

MF-XXX -Merlin Fuel



Version: 1
Revision date: 12/05/2016

Page 10 of 11
Print date: 12/05/2016

Classification codes:

Acute Tox. 3 [Dermal] : Acute toxicity (Dermal), Category 3
Acute Tox. 3 [Inhalation] : Acute toxicity (Inhalation), Category 3
Acute Tox. 3 [Oral] : Acute toxicity (Oral), Category 3
Acute Tox. 4 [Oral] : Acute toxicity (Oral), Category 4
Flam. Liq. 2 : Flammable liquid, Category 2
Flam. Liq. 3 : Flammable liquid, Category 3
STOT SE 1 : Specific target organ toxicity following a single exposure, Category 1

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Labelling in accordance with Directive 1999/45/EC:

Symbols:



R Phrases:

R5 Heating may cause an explosion.
R11 Highly flammable.
R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.
R39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.

S Phrases:

S4 Keep away from living quarters.
S16 Keep away from sources of ignition - No smoking.
S20 When using do not eat or drink.
S28 After contact with skin, wash immediately with plenty of ... (to be specified by the manufacturer).
S46 If swallowed, seek medical advice immediately and show this container or label.
S63 In case of accident by inhalation: remove casualty to fresh air and keep at rest.
S1/2 Keep locked up and out of the reach of children.

Contains:

nitromethane
methanol

Abbreviations and acronyms used:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
BCF: Bioconcentration factor.
CEN: European Committee for Standardization.
DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
EC50: Half maximal effective concentration.
PPE: Personal protection equipment.
IATA: International Air Transport Association.
IMDG: International Maritime Code for Dangerous Goods.
LC50: Lethal concentration, 50%.
LD50: Lethal dose, 50%.
Log Pow: Logarithm of the partition octanol-water.
NOEC: No observed effect concentration.
PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.
RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) No 453/2010)

MF-XXX -Merlin Fuel



Version: 1
Revision date: 12/05/2016

Page 11 of 11
Print date: 12/05/2016

<http://echa.europa.eu/>

Regulation (EU) No 453/2010.

Regulation (EC) No 1907/2006.

Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.